



Declaration of Performance

Nr SO/02/D400/E600/2016

1. DoP Reference Number:	STORA-DRAIN OPTIMA SO
2. Product serial number(s) according article 11/4:	STORA-DRAIN OPTIMA / width / height / number of pallet according label on pallet
3. Intendent use:	<p>Polyster concrete draingae channel type M for collection and conveyance of surface water from areas: caarigeways of roads (including pedastrian streets), hard schoulders and parking areas. Drainage channels system with galvanized or stainless steel protective profiles. Channels with iron cast gratings D400/E600.</p> <p>Article numbers according catalogue of products STORA-DRAIN" nominal width B=150; B=200 lenght L= 500 and 1000 mm height H= 195 - 245 mm</p>
4. Manufacturer and priduction place according article 11/5:	<p>O.P.S.O. Sp. z o.o. ul. Spółdzielcza 58; 58-500 Jelenia Góra; Poland</p> <p>Production place: O.P.S.O. Sp. z o.o. ul. Spółdzielcza 58; 58-500 Jelenia Góra; Poland</p>
5. Authorized Representative:	Not Applicable
6. Assesment and verifycation of constancy of performance:	System 3
7. Notified body that performed Type Test:	<p>Baustofftechnologie EMS GmbH, Warendorf Kiwa Zemplabor, Beckum Labor Number: 1032 Type test report reference No: 15/0435/WP-1; 15/0435/WP-2; 15/0435/WP-3; 15/0435/WP-4; 15/0435/WP-5; 15/0435/WP-6 16/0137/WP-1; 16/0137/WP-2; 16/0137/WP-3;</p>
8. First year of CE marking:	2015

9. Essential characteristics:

Essential characteristics	Properties	Relevant Harmonised Standard
Characteristics a) load bearing capacity b) permanent deformation	class D400/E600 kN 600 max.300mm/50	PN-EN 1433:2005 + PN:EN 1433:2005 + A1:2007
Water - Tightness	- pass	
Durability	N	

10. The performance of the product(s) identified in point 2 and 3 in conformity with the declared performance in point 9.
 This decalarton of performance is issued under the sole responsibility of the manufacturer identified in point 4.


